



**MOUNTING ACCESSORIES see section 8 and 10**

Material	Connections			Part no.
	Inlet	Outlet	Vent / Calibrate connection	
steel st. st.	1/2 NPT female		1/4 NPT female with screw plug	N 342.44.183.21 N 342.44.483.21
steel st. st.	1/2 NPT female	swivel nut G 1/2		N 342.44.183.22 N 342.44.483.22

Components	Steel	Stainless steel <sup>1)</sup>
	DIN - Material Number	
Body <sup>2)</sup>	1.0460	1.4404
Bonnet	1.0501	1.4571
Valve stem	1.4104	1.4571
Needle tip <sup>3)</sup>	1.4122 <sup>4)</sup>	1.4571
Packing	PTFE up to 200°C special packing up to 400°C	
Gland nut	1.0501	1.4301
T-handle	stainless steel	
Screw plug	1.0501	1.4404

- Surface: steel phosphatized
- External stem thread
- Stem with cold rolled surface, back seat and non-rotating needle tip
- Special types are available
- The manifolds can be supplied according to NACE-standard

1) Can also be supplied for oxygen service. Please notice order instruction B 3!  
 2) Available with inspection certificate 3.1.B acc. to EN 10 204  
 3) Also available with soft tip in KEL-F® (PCTFE) or Delrin® (POM)  
 4) 1.4122 quenched and tempered